



HOLLOW CORE FLUSH PANEL

SPECIFICATION BREAKDOWN

- Custom size doors, up to 3.3m high X 1.6m wide. Larger than these require our Kitform™ construction.
- Also referred to as LIGHT WEIGHT.
- Minimum of 4.75mm skins. Door builds and thicknesses refer to table at bottom right.
- Skin options: Raw MDF, Pre-Primed MDF, HMR MDF (high moisture resistant)
- Internal frame options (door edge):
- Hoop pine 30mm + 70mm MDF Lock Blocks both sides, recommend for hinge prepping and lockset face plates
- MDF 40mm + 70mm MDF Lock Blocks

OPTIONAL EXTRA'S

- Timber veneer finishes to door faces
- Laminate finishes applied to faces
- Solid Timber or Laminate edge strips
- Base seal prep's
- Mortise lock preps
- Vent grille cutouts
- Non-combustible cladding to one side (service cupboard applications)
- Stainless steel kick plates rebated into door face
- RHS verticals inside edge stiles
- Other miscellaneous hardware preps can be requested

HOW TO SPECIFY

"Nexdor Systems— Hollow Core Construction [thickness]mm thick flush panel.

With [optional extra's required]."

HOLLOW CORE - DOOR THICKNESS

		SKIN		
		4.75 MDF		
CORE	25.2	34.7		
	27.8	37.3		
	30.2	39.7		
	33.2	42.7		
	38.2	47.7		